

PC 945



BRUTE FORCE™ THE STRONGEST



TYPICAL APPLICATIONS

- Hold More, Do More.™
- For the most extreme applications, such as securing, hauling, binding, repairing, holding, and more
- Can be used as an alternative to ropes and chains in many applications

PRODUCT FEATURES

- The Bold Next Step in Tape Technology
- Built with Forge-Link™ Technology, an extreme tensile cloth – one loop holds 700+ pounds* of weight
- High-tensile strength
- Ferocious construction with high-tack, double-thick adhesive that sticks to rougher and dirtier surfaces
- Too tough to tear by hand

CONSTRUCTION

Overall Grade/Function: Super Tough
 Backing: Durable Waterproof Backing
 Adhesive: Natural Rubber

STANDARD WIDTH(S)

1.88 in

STANDARD LENGTH(S)

25 yd

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.




COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	250 lbs/in width	437.8 N/10 mm
Adhesion to Stainless Steel	65 oz/in width	7.11 N/10 mm
Thickness	17 mils	0.43 mm
Elongation	21%	21%
Service Temperature Range	32 F to 200 F	0 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*1 yard of tape looped to itself. Tape not weight rated for towing applications, visit T-RexTape.com for details.

